



TROYLUBE SHIELD

10W/40 SL/CF

Semi Synthetic

TROYLUBE SHIELD 10W/40 is semi-synthetic engine oil obtained by blending high quality base oils and additives. It can be used in gasoline, diesel and LPG vehicles which meet the ACEA A3 / B4 performance level in four seasons. It is especially recommended for use in passenger cars, light commercial and 4WD vehicles.

Properties

- Prevents deposit formation and keeps the engine clean with its effective detergent and dispersant additives.
- Provides fuel economy with its excellent viscosity control feature.
- Provides high engine power by minimizing friction inside the engine thanks to its active lubrication feature.
- It facilitates cold working with its low temperature fluidity.

Approvals and Specifications

- API SL/CF
- ACEA A3/B3, A3/B4
- MB Approval 229.3
- VW 502.00 / 505.00
- BMW LL-98
- AVTOVAZ LADA cars

Technical Specifications

Test	Method	Typical Properties
Density (15 °C), g/cm ³	ASTM D1298	0,870 – 0,888
Kinematic Viscosity (100°C), [cSt]	ASTM D445	12,5 - 16,3
Viscosity Index	ASTM D2270	Min. 140
Flash Point, °C	ASTM D92	Min. 210
Pour Point, °C	ASTM D97	Max. -30